

ARYENVARSHA DOMESTIC MODELS

ARYENVARSHA REGENERATIVE SELF PRIMING PUMPS

1 - Phase, 240 Volts, 50Hz, AC Supply, Conn : CSR, TEFC, CI Body, Class 'B', S1 Duty.

S.No	Model	Motor KW/HP	Amps	Run - Cap	Pipe Size (mm)	Rated Head in (m)	Rated in (LPH)	Head Range in (m)	Discharge in (LPH)	Shut off in (m)
1	VSP 375	0.37/0.5	3	10 mfd, 440 V AC	25 x 25	16	1050	12 - 24	2000 - 900	34
2	VSP 425	0.37/0.5	3	10 mfd, 440 V AC	25 x 25	14	1200	6 - 18	1500 - 800	25
3	VSP 725	0.75/1.0	6.5	15 mfd, 440 V AC	25 x 25	30	1200	15 - 35	2800 - 1000	45



Model : VSP 375 - 0.5 HP



Model : VSP 425 - 0.5 HP



Model : VSP 725 - 1HP

ARYENVARSHA CENTRIFUGAL MONOBLOCK PUMPS

1 - Phase, 240 Volts, 50 Hz, AC Supply, Conn : CSR, CI Body, Class 'B', S1 Duty.

S.No	Model	Motor KW/HP	Amps	Run - Cap	Pipe Size (mm)	Rated Head in (m)	Rated in (LPS)	Head Range in (m)	Discharge in (LPH)	Shut off in (m)
1	ASM 425	0.37/0.5	3	10 mfd, 440 V AC	25 x 25	15	0.9	8 - 18	5000 - 2500	22
2	ASM 725	0.75/1.0	8.5	25 mfd, 440 V AC	25 x 25	22	1.2	16 - 26	6000 - 4000	28
3	DMA 2N	0.37/0.5	3	12.5 mfd, 440 V AC	25 x 25	20	0.42	17 - 21	1700 - 1350	31



Model : ASM 425 - 0.5 HP



Model : ASM 725 - 1 HP



Model : DMA 2N - 0.5 HP

ARYENVARSHA OPENWELL SUBMERSIBLE PUMPS

1 - Phase, 240 Volts, 50 Hz, AC Supply, Conn : CSR, Wet Type, Class 'B', S1 Duty.

S.No	Model	Motor KW/HP	Amps	Run - Cap	Pipe Size (mm)	Rated Head in (m)	Rated in (LPH)	Head Range in (m)	Discharge in (LPH)	Shut off in (m)
1	ASW 525	0.37/0.5	6	36 mfd, 440 V AC	25 x 25	18	3300	15 - 22	5000 - 2500	24
2	ASW 725	0.75/1.0	7.5	50 mfd, 440 V AC	25 x 25	25	4000	21 - 26	4900 - 3100	33



Model : ASW 525 - 0.5 HP



Model : ASW 725 - 1 HP